

## Installation Instructions

Slide UM3 mount over your “Cleared” muzzle of the firearm. Make sure the spring loaded detent is engaged on the firearms mil-std 1913 tactical rail. With your thumb and index finger squeeze the top of the sight/scope mount together and then place your sight/scope securely engaged on top of the scope mount. Tighten the scope making sure the top of the mount is fully closed.

**NOTICE:** After installation of the UM3 Sight Mount on your firearm, the slide of the firearm must be manually cycled one or two times in order to confirm taller factory or aftermarket iron sights are NOT installed on the firearm.

## Cautions & Warnings

**CAUTION:** When installing/removing the UM3 mount from your firearm or adjusting any mounted optic be absolutely sure that the firearm is completely unloaded and pointed in a safe direction. Follow the procedure for “Unloading” and “Cleaning” in your firearm’s manual.

**CAUTION:** Always wear proper eye and ear protection when shooting your firearm.

**NOTICE:** The UM3 Sight Mount may not be used on guns with elevated, tall or high front sights.

**Use of the UM3 Mount with compensated/ported handguns:** The UM3 mount is compatible with many compensated/ported handguns. The location of the porting is the determining factor in deciding if a specific handgun is appropriate to use with the UM3 mounting system. If the exhaust gasses are vented forward of the leading (front) edge of the UM3 mount then your handgun is appropriate to use with the UM3 mount. However, if your handgun is designed in such a way that the vented gasses would be directed under or into the inside of the UM3 mount then that specific handgun is inappropriate for use with the UM3 mounting system.

## Installation Instructions

Slide UM3 mount over your “Cleared” muzzle of the firearm. Make sure the spring loaded detent is engaged on the firearms mil-std 1913 tactical rail. With your thumb and index finger squeeze the top of the sight/scope mount together and then place your sight/scope securely engaged on top of the scope mount. Tighten the scope making sure the top of the mount is fully closed.

**NOTICE:** After installation of the UM3 Sight Mount on your firearm, the slide of the firearm must be manually cycled one or two times in order to confirm taller factory or aftermarket iron sights are NOT installed on the firearm.

## Cautions & Warnings

**CAUTION:** When installing/removing the UM3 mount from your firearm or adjusting any mounted optic be absolutely sure that the firearm is completely unloaded and pointed in a safe direction. Follow the procedure for “Unloading” and “Cleaning” in your firearm’s manual.

**CAUTION:** Always wear proper eye and ear protection when shooting your firearm.

**NOTICE:** The UM3 Sight Mount may not be used on guns with elevated, tall or high front sights.

**Use of the UM3 Mount with compensated/ported handguns:** The UM3 mount is compatible with many compensated/ported handguns. The location of the porting is the determining factor in deciding if a specific handgun is appropriate to use with the UM3 mounting system. If the exhaust gasses are vented forward of the leading (front) edge of the UM3 mount then your handgun is appropriate to use with the UM3 mount. However, if your handgun is designed in such a way that the vented gasses would be directed under or into the inside of the UM3 mount then that specific handgun is inappropriate for use with the UM3 mounting system.